

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

CORRECTED VERSION

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
9 October 2003 (09.10.2003)

PCT

(10) International Publication Number  
**WO 03/083349 A1**(51) International Patent Classification<sup>7</sup>: **F16M 1/00**,  
B01F 13/10(Modena) (IT). **FIFIELD, Bruce** [US/IT]; Via Crema, 15,  
20135 Milano (IT).

(21) International Application Number: PCT/IB03/01160

(74) Agent: **PROVVISIONATO, Paolo**; Provvisionato & Co  
S.r.l., Piazza di Porta Mascarella, 7, 40126 Bologna (IT).

(22) International Filing Date: 25 March 2003 (25.03.2003)

(25) Filing Language: Italian

(26) Publication Language: English



(30) Priority Data:  
BO2002A000160 28 March 2002 (28.03.2002) IT(71) Applicant (for all designated States except US): **CPS  
COLOR EQUIPMENT S.P.A.** [IT/IT]; Via dell'Agri-  
cultura, 103, I-41038 San Felice sul Panaro (Modena) (IT).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GREEN, Gordon**  
[IT/IT]; Via Loschi, 13, 41038 S. Felice sul Panaro (Modena) (IT).(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD,  
SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US,  
UZ, VC, VN, YU, ZA, ZM, ZW.  
(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,  
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,  
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MACHINE STRUCTURE, IN PARTICULAR FOR HANDLING FLUID PRODUCTS, AND PROCESS FOR ASSEMBLING IT



(57) Abstract: A machine structure, in particular for the processing of fluid products, comprises a loadbearing frame with vertical uprights (12) connected by two horizontal plates (14,15) at a distance from each other. Between the uprights are located one or more removable covering panels (13) which cover the zone housing the machine components. The machine structure is strong but light, not very bulky and easy to assemble even by non-specialist personnel.

Best Available Copy

WO 03/083349 A1

**Declarations under Rule 4.17:**

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)*

- *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

- *with international search report*

**(48) Date of publication of this corrected version:**

20 November 2003

**(15) Information about Correction:**

see PCT Gazette No. 47/2003 of 20 November 2003, Section II

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

MACHINE STRUCTURE, IN PARTICULAR FOR HANDLING FLUID PRODUCTS,  
AND PROCESS FOR ASSEMBLING IT

This invention relates to a machine structure, in particular but not restricted to machines for the handling of fluid products. The invention has been developed with particular reference to structures which contain, protect and enclose the mechanisms of machines such as for example machines dispensing dyes or machines mixing fluid products, for example paints, varnishes, enamels, inks and the like contained in cans, drums and containers of that nature. The invention also relates to a process for assembling the above-mentioned structure.

Machines of the type indicated above are normally housed and supported by frame structures which generally comprise bars, cross-members and uprights welded together to form a frame having a particular shape and dimensions. After the mechanical, electronic and working parts of the particular machine have been placed within the frame, this is normally covered with panels secured to the structure of the frame by connection systems of a known type such as screws, bolts and, in some cases, hinges or the like to allow the panels to be at least partly opened so that the components of the machine can be inspected.

One disadvantage of frame structures of the known type indicated above lies in the fact that these are not particularly flexible in construction and therefore fit with difficulty into cramped spaces, such for example the points of sale where such machines have to be used. Normally, machines of the known type have a one-piece structure with little modularity and are not particularly pleasing from the aesthetic point of view.

Another disadvantage of machine structures of the known type comprises the fact that they must be assembled and set up in the workshop and then transported in the assembled state to the place where they will be used, with a consequent increase in costs and times for transport.

The purpose of this invention is to overcome the problems of the known art and in particular to provide a machine structure and a process for assembling it which is simple, economical and easy to apply in the place where the machine is used, even by not particularly specialised personnel.

Another purpose of this invention is to provide a machine structure which when assembled is of small size and can be easily and flexibly adapted to the special space, shape and positioning requirements of all places where the machine is in use.

In order to achieve the above-mentioned purposes, the invention relates to a machine structure, in particular a machine for the handling of fluid products, comprising:

- a loadbearing frame including uprights, and
- one or more covering panels,

characterized in that the uprights extend in a substantially vertical direction and have an upper end to which or close to which there is fixed a first substantially horizontal plate for connecting the uprights, a second substantially horizontal plate being attached to the same uprights to connect them in a zone lying beneath the first plate and thus forming a zone within which the machine's mechanisms are housed, at least one of the covering panels being dismantlably mounted between two uprights to at least partly cover the housing zone laterally.

The invention also relates to a special kit and procedure for assembling the above-mentioned structure having the features indicated in claims 13 and 14 below respectively.

An advantage of this invention which derives from its modular nature and the easy assembly of the machine structure is the possibility of quickly and simply hooking on and replacing the side panels which form the sides of the structure. In this way the machine structure can be personalised with very little effort, so that its aesthetic features can be matched to the special environment in which it has to be placed. In addition to this side panels can be constructed with slogans or inscriptions and advertising images, which are easily replaceable and interchangeable, for example for the promotion of special events, offers, bargains and the like.

Another advantageous feature of this invention lies in its ergonomic nature, and in particular in its especially convenient configuration for use by a seated operator. The features of the structure according to this invention make it possible to adjust it quickly and effectively to any special anthropometric characteristics of the operator, merely by altering the height of the uprights, without thereby having to act on the other parts of the machine structure.

According to a further particularly advantageous feature the structure according to this invention has three uprights and has a substantially triangular configuration in plan, preferably having sides with convexity away from the machine. In addition to being aesthetically attractive this configuration constitutes a very useful solution for locating the machine structure in the corner of a room, so as to make the optimum use of space and nevertheless provide a wide frontal surface for access to the machine.

In a possible configuration of the machine structure according to the invention it is provided that a first plate should be secured to the top ends of the uprights and the second plate should be secured to a middle zone of these uprights. In this way the machine and its mechanical components are raised off the ground, in an ergonomic position for an erect operator. The empty space beneath the second plate can be used as a locker, and in this case the zone lying beneath the second plate can advantageously be at least partly covered laterally by side panels which extend to the ground from the tops of the uprights.

The machine structure according to this invention can be advantageously used to house a complex of dispensing units for colouring agents of a generally known type, for example of the type described in document EP-A-1030972. In this case the tanks of colouring agent for each dispensing unit can be attached ~~connected~~ to the first upper plate of this invention.

In the case where the structure according to this invention houses the mechanisms of a dispensing machine, the dispensing zone may comprise a recess in the panel or panels covering the front part. In this way the overall dimensions of the machine, especially in plan, remain small, and in addition to this protection is provided for the dispensing nozzle.

In accordance with a further advantageous feature of this invention it is possible to provide a supporting plane for containers of colouring agent, designed to receive the product delivered, constituting for example a table which is preferably mounted to hinge against or disappear beneath the dispensing zone.

Other advantages and characteristics of the present invention will become clear from the following detailed description

which is given with reference to the appended drawings which are provided purely by way of non-limiting example and in which:

- Figure 1 is a perspective view of a first embodiment of a machine structure according to this invention,
- Figure 2 is a perspective view of another possible embodiment of a machine structure according to the invention,
- Figure 3 is a perspective view similar to that in Figure 1, illustrating the machine structure without its side covering panels,
- Figure 4 is a transverse cross-section through the structure in Figure 1,
- Figure 5 is a view in lateral elevation of a variant of this invention which for clarity of illustration is shown without the covering side panels,
- Figure 6 is a view along arrow VI in Figure 5,
- Figure 7 is a perspective and exploded view of the structure in Figures 5 and 6, and
- Figure 8 is a transverse cross-section on a magnified scale of the upright for the machine structure in Figures 5 to 7.

With reference now to Figure 1, a machine structure 10 comprises a loadbearing frame 11 which includes substantially vertical uprights 12 supported on the ground to support the machine structure. As a whole the machine mechanisms, of a type which is generally known and which are therefore not further described and discussed in this description, are housed in the space bounded by side panels 13, preferably hooked onto uprights 12, an upper plate 14 and a lower plate 15.

Depending upon the type and configuration of the machine components and mechanisms intended to be housed in structure

10, an access space or a working area, for example comprising a supporting plane 17, preferably mounted so that it can be drawn out with respect to the front part 16 of the machine structure may be provided in the frontal zone 16 of structure 10.

Figure 2 shows a different embodiment of structure 10 for machines in which one or more side panels 13a extend from the upper end of uprights 12 to the ground, substantially forming a semi-enclosed space 18 below lower plate 15 which forms the lower boundary for the zone housing the machine components.

As it will be better seen in Figure 3, in the preferred embodiment of the invention each upright 12 comprises a principal portion 19 which extends from the ground to the very top of machine structure 10. Principal portion 19 is preferably of a folded shape, having a flat central part 20 from which two wings 21 which are folded at their ends to form a longitudinal hook 22 extend laterally. A secondary portion 23 of upright having a shape which substantially corresponds to that of principal portion 19 and to which it is fixed back to back preferably extends from the ground to a median zone of principal portion 19, at which point lower plate 15 is fitted. Upper plate 14 is also fixed to uprights 12, and in particular at the tops of the principal portions 19 of uprights 12. Between plates 14, 15 and each upright 12 there is placed a folded plate 24 which together with wings 25, 26 provided along the perimeter of each plate 14, 15 comprises a stop for the side panels 13, 13a of machine structure 10.

In the particular embodiment illustrated in Figure 3, machine structure 10 is designed to receive a number of machine units M having reservoirs suspended on upper plate 14 through a plurality of shaped openings 27 made in the latter. A particular number of shaped openings 27 may be provided in



plate 14 in advance at the time of its manufacture and any shaped openings 27 which exceed the number of machine components M actually fitted on the machine can be covered by a film or sheet 28.

Figure 4 clearly shows the function of longitudinal hooks 22 of uprights 12 and the manner in which they act together with corner plates 24 to secure restrainingly support side panels 13, 13a and at the same time impart to them a curvature with a convexity away from the zone in which the components of machine M are housed.

Machine structure 10 described above can easily be delivered to the point of final use in a dismantled state. In particular an assembly kit comprising uprights 12, preferably but not limited in number to three, the two plates 14 and 15, a particular number of machine components M intended to be housed in machine structure 10, side panels 13, 13a and the connecting components (screws, bolts, nuts, washers, etc.) normally provided for the assembly of structures in kit form can be supplied.

At the time of assembly it is only necessary to secure the two plates 14, 15 to uprights 12. In particular upper plate 14 is secured close to one end of each upright 12, while lower plate 15 is secured at a predetermined distance from the aforesaid end of each upright 12. After having housed the components of machine M within the space defined by the two plates 14, 15, in particular suspending the reservoirs illustrated in the embodiment in Figure 3 from upper plate 14 after having caused them to pass through shaped openings 27, it is only necessary to cover the sides of machine structure 10 with side panels 13 restrained between two adjacent uprights 12. Side panels 13 are preferably held in a covering position by longitudinal hooks 22 provided on the uprights

## 8

and/or a set of channels or hooks or other means of connection provided on the periphery of plates 14, 15.

If necessary, uprights 12 can also be shortened at the place where machine structure 10 will finally be used in order to make the height of the machine structure suitable for the particular dimensions of the location or the anthropometric measurements of the final user. In some cases it is possible to fit lower plate 15 close to or at the ends of uprights 12 opposite those to which upper plate 14 is fixed, thus forming a completely enclosed machine structure 10 which is particularly suitable for being supported on a working surface.

In the configurations illustrated in Figures 1 and 2, in which lower plate 15 is secured in an intermediate zone of uprights 12, the zone beneath lower plate 15 can also usefully be used to house other working machines, such as for example a machine mixing the fluid products which are to be used in combination with any machine dispensing the fluid products and/or colouring agents housed within frame 11 and protected by side walls 13, 13a, in addition to objects of various kinds.

Again in the configurations illustrated in Figures 1 and 2, supporting plane 17 is preferably mounted so that it can be drawn out from the lower surface of lower plate 15, so that it can be drawn therefrom when necessary to support containers of colouring agent in the delivery zone. Supporting plane 17 can then be caused to disappear beneath plate 15 when not in use in order to reduce the frontal dimensions of the machine structure. Of course this advantage may be obtained using equivalent solutions, for example with a supporting plane of the tilting type, hinged to the machine structure.

Figures 5, 6 and 7 illustrate a second preferred embodiment of machine structure 10, in which the same reference numbers are used to indicate parts corresponding to those previously described. Within the zone housing the components of machine M there are placed bracing ties 30, preferably two in number, in order to stiffen the structure as a whole. The two ties 30 preferably but not limited thereto both have one of their ends 30a connected to the same upright 12 through a connection plate 31 or other similar means of connection, while their opposite ends 30b are each respectively connected in a similar way to one of the other uprights 12.

In the embodiment illustrated in Figures 5, 6 and 7, lower plate 15 is mounted on the opposite end of uprights 12 to that to which plate 14 is secured. In this way machine structure 10 is particularly suitable for being supported on working surfaces, benches or shelves already present at the place where the machine structure is to be installed. On its front, the machine structure comprises a first panel 13b, of a lesser height than side panels 13. Below front panel 13b is located another panel 35 to complete covering of the front part of the machine structure. Lower panel 35 is re-entrant towards the zone where the components of machine M are housed, in relation to overlying panel 13b, so as to form a space to define a dispensing zone. Behind front panel 13b it is possible to house a support 47 fixed laterally to uprights 12 on which for example are placed devices 48 to control the components of machine M and if necessary to display the operating status of the same.

A shape 36 is made in panel 13b to allow the dispensing nozzle of the machine to project. A cap 37, overlying the upper part thereof and following shape 36, is then provided for protection of the nozzle. A shaped plate 38 is located horizontally to connect lower panel 35 and front panel 13b, and has a hole 32 for the dispensing nozzle. Below shaped

plate 38 is preferably connected a device for moistening nozzles 39, commonly known as an "autocap", for example of the type which is the subject matter of patent US-A-5842641 by the same applicant, the description of which is understood to be incorporated here for reference.

In this variant uprights 12 are each constructed of a single component whose preferred cross-section, though without being restricted thereto, is illustrated in Figure 8. This cross-section has a first closed central portion 40 flanked by wings 21, also closed, on each of which is provided a longitudinal hook 22. On the back 20 of central portion 40, as also in the connection zone between central portion 40 and wings 21, there are shaped channels 41 which extend longitudinally over the entire length of the upright. The cross-sections of channels 41 are such as to receive securing components such as nuts and the like, and have appendages 42 which retain such securing components, at the same time forming openings 33 for passage of the shanks of bolts and the like (not illustrated) for holding lower and upper plates 14 and 15 in position. By slackening off the securing components which are partly engaged in shaped channels 41 it is possible to adjust the longitudinal positions of the plates and position them at a desired height along uprights 12.

As shown in Figure 7, shaped openings 27 provided in upper plate 14 can be at least partly covered by a rigid shaped plate 45 positioned at the top of machine structure 10. As already described above with reference to covering sheet 28 in Figure 3, only the shaped openings 27 actually used for housing the components of machine M can also be provided in rigid plate 45, thus preventing the entry of contaminating agents through the other openings and improving the overall aesthetic appearance of machine structure 10.

Again with the object of improving the appearance of the machine structure, covers 46, shaped according to the cross-section of uprights 12, are inserted into the ends of uprights 12.

Naturally, the principle of the invention remaining the same, the forms of embodiment and details of construction may be varied widely with respect to those described and illustrated, which have been given purely by way of example, without thereby departing from the scope of the invention.

CLAIMS

1. A machine structure, in particular for a machine for handling fluid products, comprising:

- a loadbearing frame including uprights, and
- one or more covering panels,

characterized in that the uprights (12) extend in a substantially vertical direction and have an upper end close to or onto which is secured a first substantially horizontal plate (14) for connecting the uprights (12), a second substantially horizontal plate (15) being secured to the same uprights (12) to connect them in a zone beneath the first plate (14, 15) and thus form a zone for housing the mechanisms of the machine (M), at least one of the covering panels (13, 13a) being removably fitted between two uprights (12) in a covering position to at least partly cover the housing zone laterally.

2. A structure according to claim 1, characterized in that the uprights (12) have longitudinal connection means (22) for restraining said covering panels (13, 13a).

3. A structure according to claim 1 or 2, characterized in that one or both plates (14, 15) have peripheral connection means to at least partly support at least one side panel (13, 13a) in the covering position.

4. A structure according to claim 1 or 2, characterized in that it comprises three uprights (12).

5. A structure according to claim 1, characterized in that at least one covering panel (13, 13a) has a curvature with convexity away from the housing zone.

6. A structure according to any one of the preceding claims, characterized in that the second plate (15) is secured in a median zone of the uprights (12).
7. A structure according to claim 6, characterized in that the covering panels (13, 13a) extend vertically over a distance which is substantially equal to the distance between the two plates (14, 15).
8. A structure according to claim 6, characterised in that at least one side panel (13a) extends over a length substantially equal to the height of the upright (12).
9. A structure according to any one of the preceding claims, characterized in that it has a frontal zone (16) for working access to the functions of the mechanisms of the machine (M) housed within the structure.
10. A structure according to claim 9, characterized in that it has a working surface or support (17) provided in the front zone (16), mounted so that it can be drawn out or moved to disappear, or tilted.
11. A structure according to any one of the preceding claims, characterized in that the first upper plate (14) comprises a plurality of shaped openings (27) to house and support components of the machine (M).
12. A structure according to claim 11, characterized in that it comprises a covering member (28, 45) located on the first upper plate (14) to at least partly cover one or more shaped openings (27).
13. A structure according to any one of the preceding claims, characterized in that it comprises bracing ties (30) which connect the uprights (12) together.

14. An assembly kit for constructing a machine structure according to any one of claims 1 to 13, characterised in that it comprises:

- two or more elongated uprights (12),
- at least two plates (14, 15) connecting the uprights (12), connecting members to secure the plates (14, 15) to the uprights (12) at a predetermined distance, and
- one or more side covering panels (13, 13a) each designed to be restrained between two uprights (12).


15. A process for the assembly of a machine structure according to any one of claims 1 to 13, characterized in that it comprises the stages of:

- mounting the first upper plate (14) close to one end of each upright (12),
- mounting the second plate (15) on uprights 12 at a predetermined distance from the said end of each upright (12),
- mounting the components of machine (M) in the housing zone formed between the first (14) and the second (15) plate, and
- mounting the side covering panels (13, 13a) each between two adjacent uprights (12).




1/7

FIG.1



2/7

FIG. 2



3/7




FIG. 3

4/7




FIG. 4

5/7




FIG. 5




FIG. 6

6 / 7




FIG. 7

7/7




FIG. 8

## INTERNATIONAL SEARCH REPORT

Intern. Application No

PCT/IB 03/01160

**A. CLASSIFICATION OF SUBJECT MATTER**  
 IPC 7 F16M1/00 B01F13/10

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 F16M B01F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 309 365 A (VAN NESS DAVID ET AL) 5 January 1982 (1982-01-05) column 5, line 1 - line 47; figures 1-12	1-3, 14, 15
A	---	7, 8
X	US 3 307 894 A (DAVID COLLIER) 7 March 1967 (1967-03-07) column 3, line 54 - line 75; figures 1, 2	1, 14, 15
	---	7, 8
X	US 4 354 330 A (SCHWARTZ WESLEY W) 19 October 1982 (1982-10-19) column 4, line 49 - column 5, line 24; figures 5-9	1, 2, 4, 11, 14, 15
	---	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

**\* Special categories of cited documents:**

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

\*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

\*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

\* & \* document member of the same patent family

Date of the actual completion of the international search

28 July 2003

Date of mailing of the international search report

04/08/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
 NL - 2280 HV Rijswijk  
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
 Fax: (+31-70) 340-3016

Authorized officer

Baron, C



## INTERNATIONAL SEARCH REPORT

International Application No.

PCT/IB 03/01160

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	EP 1 093 842 A (ESMORIS RODRIGUEZ MARIA JESUS) 25 April 2001 (2001-04-25) column 3, line 51 -column 4, line 16; figures 1,2 -----	1,5-7,9
A	WO 99 19628 A (MAZZALVERI LEOPOLDO ;COROB SPA (IT); PARRINO ANDREA (IT); MANFREDI) 22 April 1999 (1999-04-22) & EP 1 030 972 A 30 August 2000 (2000-08-30) cited in the application -----	

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Interr | Application No

PCT/IB 03/01160

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4309365	A	05-01-1982	US 4419300 A	06-12-1983
US 3307894	A	07-03-1967	GB 1101356 A	31-01-1968
			CH 443423 A	15-09-1967
			NL 6505661 A	05-11-1965
US 4354330	A	19-10-1982	NONE	
EP 1093842	A	25-04-2001	EP 1093842 A1	25-04-2001
			AT 239543 T	15-05-2003
			DE 69907680 D1	12-06-2003
WO 9919628	A	22-04-1999	IT 80970609 A1	13-04-1999
			AU 1029799 A	03-05-1999
			BR 9813032 A	15-08-2000
			CN 1276040 T	06-12-2000
			WO 9919628 A1	22-04-1999
			EP 1030972 A1	30-08-2000
			JP 2001520350 T	30-10-2001
			NO 20001878 A	13-06-2000
			US 2002195462 A1	26-12-2002
			US 6457607 B1	01-10-2002

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**